

MiniBREAK MB1-38M-FP

The MiniBREAK single pump packaged tank and booster set has been designed to be compact and provide fluid cat 5 backflow protection via an 'AB' air gap. It complies with the water supply (water fittings) regulations 1999 and comes as a complete package in an enclosed cabinet suitable for wall or floor mounting.

The pump control is provided by a well-proven intuitive controller that will start the pump at falling pressure and stop the pump when flow ceases. The control unit also provides low water protection.

Pre-fitted with integral thermostat and heater for frost protection.

VOLT-FREE CONTACTS PUMP RUNNING

Both open and closed volt-free contacts are available, which indicate if the pump is running. See the appropriate drawing for volt-free contact wiring configurations.

PRODUCT OVERVIEW

- Volt-free contact for pump running
- IP65-rated controller
- Lockable enclosure
- Low-water protection device
- Wall or floor mountable
- Single phase

APPLICATIONS

- Wash down in bin stores
- Dentist's rinsing equipment
- Laboratory water supplies
- Single hosepipe supplies
- Any application where cat 5 protection is required mortuaries, abattoirs, zoos, healthcare premises, etc.

DUTYPOINT STANDARD WARRANTY

Your Dutypoint Systems standard product warranty is valid for a period of 24 months from date of despatch. If you need to contact us regarding your warranty or any issues regarding your Dutypoint product, please contact our service department. Call 01452 300590, email service@dutypoint.com or visit dutypoint.com/service.



RANGE PERFORMANCE

Number of pumps	1
Typical duty	0.2 l/s @ 2.5 bar 0.3 l/s @ 1.8 bar 0.4 l/s @ 1.2 bar
Break tank capacity	23 litres
Noise data	Motor at < 70 LpA (dB +/-2)*


^{*}More specific details available on request.

MATERIAL SPECIFICATION

Housing	LDPE
Pump body	PPE and brass
Pipework and fittings	Copper, brass, stainless steel
Weight	MB1-38M-FP = 21 kg









0.1

0.5

20

0

0

0

0.2

0.3

Flow

 m^3/h

l/s

1.5

0.5

0.4