



ResiSHIELD DK Fire Sprinkler Pump Set

BS 9251:2021 compliant





Designed for the single dwelling domestic market.

PRODUCT OVERVIEW

- Domestic (Cat 1) application
- Full kit of components
- Common models are available from stock
- **–** BS 9251:2021 compliant

Key Features



Specification

Compact and flexible fire sprinkler pump kits for domestic applications.

PRODUCT OVERVIEW

- Full kit of components, giving the installer flexibility to locate the pump, panel and manifold in different places
- **BS** 9251:2021 compliant for Cat 1 sprinkler systems
- High-quality cast stainless steel manifold assembly
- Supplied within a single compartmentalised cardboard box for easy storage and handling
- Volt-free contacts included for fire alarm and range of faults
- Intuitive LCD controller with full number keypad makes set up and commissioning quick and user friendly
- Can be connected directly to the mains water supply (subject to local water authority approval)
- Common models are available from stock

RANGE PERFORMANCE

Flow range	30 - 130 l/min
Pressure range	1 - 5 bar
Max system pressure	10 bar
Starting type	DOL

MATERIAL SPECIFICATION


Manifold	Duplex stainless steel			
Non-return valve	Brass			
Pump casing	AISI 304 stainless steel			
Pump impellers	AISI 304 stainless steel			


DK03/05


DRAWINGS AND DIMENSIONS


Madalina		Supply	FI C (A)	Suction	Discharge	Pump dimensions (mm)			Total
Model no.		size	L	н	w	weight (kg)			
DK0302E-M	0.33	230/1/50	2.5	1 ¼" BSP	1" BSP	361	207	204	23
DK0303E-M	0.45	230/1/50	3	1 ¼" BSP	1" BSP	361	207	204	23
DK0304E-M	0.55	230/1/50	3.7	1 ¼" BSP	1" BSP	385	207	204	23
DK0305E-M	0.75	230/1/50	4.3	1 ¼" BSP	1" BSP	409	207	204	24
DK0502E-M	0.45	230/1/50	3	1 ¼" BSP	1" BSP	361	207	204	23
DK0503E-M	0.55	230/1/50	3.9	1 ¼" BSP	1" BSP	361	207	204	23
DK0504E-M	0.9	230/1/50	5.3	1 ¼" BSP	1" BSP	385	207	204	25
DK0505E-M	1.1	230/1/50	6.2	1 ¼" BSP	1" BSP	409	207	204	25

All DK models use Direct On Line type starting.











DK03 Series


SINGLE PUMP CURVES






DK05 Series

SINGLE PUMP CURVES





Which ResiSHIELD?

Supplied as a kit for flexibility and accommodation of tight spaces Supplied fully pre-assembled, wired and tested pump set within a compact mild steel enclosure

Fully pre-assembled, wired and tested pump set, mounted on a mild steel skid plate

DK	DH	RZ	RV
	Land State of the		

				#ens
Application	Domestic (Cat 1)	Domestic (Cat 1)	Residential (Cat 2-4)	Residential (Cat 2-4)
Duty flow range	30 – 130 l/min	30-200 l/min	30-400 l/min	150-750 l/min
Pressure	1 - 5 bar	1 - 5 bar	1 - 9.5 bar	1 - 18 bar
Availability*	Ex stock	Ex stock	2-3 working weeks	4-5 working weeks
Integrated automatic weekly test	Yes	Yes	Yes	Yes
Compliance	BS 9251:2021	BS 9251:2021	BS 9251:2021	BS 9251:2021
Options	Connection direct to mains water supply (subject to local water authority approval)	Floor or wall-mounted Connection direct to mains water supply (subject to local water authority approval)	Soft start or VFD for 7.5 kW+ Single packaged skid for Cat 4 duty/ standby systems	Handed version available at no extra cost or lead time Soft start or VFD for 7.5 kW+ Single packaged skid for Cat 4 duty/ standby systems

^{*}Lead times stated are indicative and may vary between specific models.



Let's talk about ResiSHIELD DK

01452 300110 ENQUIRIES@DUTYPOINT.COM DUTYPOINT.COM