

VQ1-05-011M

Product Description

Dutypoint Systems AirBREAK™ combined cat 5 break tank and variable speed single pump booster system. Free-standing unit comprising an insulated polyethylene tank with 90L nominal capacity with high flow failsafe motorised inlet valve controlled via probe sensors and an internal flow calming baffle to protect the pump against air locking. Control system includes an electronic variable speed pump controller, common fault and remote inhibit volt-free contacts for connection to BMS, PurgePRO™ automatic pressure vessel purging system, anti-seize protection. Unit also includes pump union, isolation and non-return valves, pressure vessel and pressure gauge.

Accreditations	<ul style="list-style-type: none"> - Water Regulations Category 5 backflow prevention compliant - KUK Reg4 Approval Pending (non-wholesome use) - WRAS Approval Pending (non-wholesome use)
Control System	<ul style="list-style-type: none"> - Conductivity probe tank level sensors - Variable speed pump controller with bluetooth for app control - Anti seize function
Protection	<ul style="list-style-type: none"> - Low level protection against dry running - Pump protection MCB - Pipework leak detection - PurgePRO™ auto pressure vessel purge function
Available Factory Fitted Optional Extras*	<ul style="list-style-type: none"> - High level alarm VFC - High temperature alarm VFC - Auto purge on high temperature function - Weir tray with waste pipe connection - 90L slave tank with inlet valves
Available Accessories*	<ul style="list-style-type: none"> - Weatherproof kiosk c/w stat and heater - GRP Drip Tray with level sensor




Specification

Inlet connection	1" BSP
Delivery connection	1 1/4" BSP
Max operating flow (per pump)	2.2 l/s
Max operating pressure	3.8 bar
Closed valve pressure	4.2 bar
Maximum system pressure rating	10 bar
Speed	Variable
IP rating	IP44
Motor power	1.1 kW
Weight	60 kg
Pressure vessels N° x [Litres]	1
Maximum operating temperature	23 °C

*For high temperature applications please contact the office.

Set Performance



DUTYPOINT

www.dutypoint.com

Electrical Data

Supply Voltage/Φ/Hz
230/1/50
Full Load Current (Per pump)
4.1 A

Model Codes

VQ1-05-011M

VQ - Variable Speed High Performance
 FQ - Fixed Speed High Performance
 FC - Fixed Speed Compact

Number of pumps

Nominal flow (m³/h)

Motor kW per pump

Power supply

Technical Drawing

